

Stainless design. Stellar performance. Superior value.

Project name:									
Location:									
Item #: QTY:									
Model #:									

AGR23 REFRIGERATOR

SINGLE DOOR GLASS REACH-IN REFRIGERATOR



AGR23

- Tested to NSF Standard 7 requirements for open food storage.
- Standard with full two year parts and labor warranty and a five year compressor warranty.
- Arctic Air products must pass numerous quality control inspections throughout the manufacturing process.
- All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas.







SINGLE DOOR GLASS REACH-IN REFRIGERATOR

Exterior cabinet construction consists of full stainless steel front and sides.

Interior cabinet is bright sls with full stainless steel floor with coved corners.

Three adjustable, heavy-duty epoxy coated wire shelves.

Self-contained capillary tube system using environmentally friendly R290 Hydrocarbon gas.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.

Front accessible, bottom mounted condensing unit is mounted on slide out rack for easy maintenance.

Easy to mount casters (two lockable) are standard with all units.

Interior LED lighting



Electronic thermostat with external digital LED display for accurate control and easy reading.

Self closing lockable door.

Magnetic door gasket is removable and replaceable without tools.

Larger fan motors and blades for more efficient air flow ensuring faster recovery times.


Bottom mounted compressor for more efficient operation in coolest area of kitchen.


Tested to NSF Standard 7 requirements for open food storage.


 Standard with full two year parts and labor warranties and a five year compressor warranty.

STAINLESS STEEL DESIGN . STELLAR PERFORMANCE . SUPERIOR VALUE

Model Number	Exte Width	rnal Dime Depth	nsions Height**	Doors	Epoxy Coated Shelves (horizontal)	Cubic Feet	Temperature Range	Cord Length	НР	AMPS	REF	NEMA Plug	Crate Weight
AGR23	27"	31.25"	83.25"	1	3	23	33°F to 41°F	8′	1/3	2.6	R290	5-15P	330Llbs









**Height includes 5" for casters