

www.atosa.com | www.atosausa.com

California, Colorado, Florida, Georgia, Illinois, New Jersey, Ohio, Texas, Washington

Atosa Smart Touch Combi Ovens











AEC-0511E

AEC-0711E

AEC-1011E

AEC-0621E

AEC-1021E

FEATURES

- 10" Smart Touch Flat Screen Large cooking process icons with clear, colorful, and vibrant graphics
- ATOSA Combi Smart Cooking Automated cabinet monitoring to maintain cooking temperature, humidity and load size
- Combi Smart Touch Processes User friendly / easy access to programmable multi-stage cooking, manual cooking core probe cooking, and menu options
- 8 Fan Speed with Balance Reverse
- Perfect Humidity Control An automatic system designed for maximizing steam saturation and humidity control
- Sub-divided Heating System For maximum recovery
- Smart Touch Rack Timing For mixed load batch cooking, banquets, buffet and a la carte restaurant service
- USB Storage Share Combi recipes, programs, and HACCP data with multiple operation units and locations
- Wi-Fi Connection Remotely monitor Combi operating status in real time with fault alarm via tablet or smart phone *
- Wi-Fi Self Diagnostics Protection Safety protections to protect and ensure oven remains in safe working order *
- Wi-Fi Service Diagnostics Remote service tech diagnostics and component trouble shooting *
- 6 Mode Automated Combi Wash Cleaning based on soil and usage to include automatic shut down and un-lock when finished
- Proprietary ATOSA Chemicals Combi wash is approved for use with ATOSA professional liquid Combi cleaners and rinse agents that comply with local laws and regulations
- Twin Chemical Fill Tanks Combi automatically reminds user to add cleaner / rinse to tanks when low without the need to check at time of cleaning
- Sleek Design Triple-pane tempered glass, condensed footprint, convenient for cleaning and maintenance
- Footless Combi Design Ergonomic footing for stability, and placement
- High-Pressure Coil Wash Hose Ideal for manual quick flush, quench, rinsing and cabinet quick cleaning

* Wi-Fi features not yet available - coming soon!



Toll Free: 855-855-0399 Email: info@atosausa.com

www.atosa.com | www.atosausa.com

California, Colorado, Florida, Georgia, Illinois, New Jersey, Ohio, Texas, Washington

SPECIFICATIONS

ATOSA SMART-TOUCH COMBI SPECIFICATIONS					
MODELS	AEC-0511E	AEC-0711E	AEC-1011E	AEC-0621E	AEC-1021E
Capacity	5 x (18 x 13) Pan or 5 x (20 3/4 x 12 3/4) Pan	7 x (18 x 13) Pan or 7 x (20 3/4 x 12 3/4) Pan	10 x (18 x 13) Pan or 10 x (20 3/4 x 12 3/4) Pan	6 x (18 x 26) Pan or 6 x (20 3/4 x 12 3/4) Pan	10 x (18 x 26) Pan or 10 x (20 3/4 x 12 3/4) Pan
Rack Slots	5	7	10	6	10
Volts	208/240	208/240	208/240	208/240	208/240
Phase	3	3	3	3	3
Amp Draw (Min/Max)	21/28	33/42	43/55	41/54	63/80
Breaker	30A	40A	60A	60A	90A
KW	7.5 - 9.9	11.9-15	15.4-19.5	14.6-19.3	22.5-28.8
Connection / AWG	L1, L2, L3, G / 6-4	L1, L2, L3, G / 6-4	L1, L2, L3, G / 4-3	L1, L2, L3, G / 4-3	L1, L2, L3, G / 2-1
Dimension (WxDxH")	31 x 34 1/2 x 28"	31 x 34 1/2 x 35"	31 x 34 1/2 x 41 1/2"	36 x 42 1/2 x 36 1/2"	36 x 42 1/2 x 48 1/2"
Weight (lbs)	209	267	300	354	436
Weight Capacity	Total = 198# 39# Per Shelf	Total = 273# 39# per Shelf	Total = 390# 39# per Shelf	Total = 390# 65# Per Shelf	Total = 650# 65# Per Shelf
Water Line Size	5/16" OD / 1" ID	5/16" OD / 1" ID	5/16" OD / 1" ID	5/16" OD / 1" ID	5/16" OD / 1" ID
Energy Star Rating		ENERGY STAR	Lough C	ENERGY STAR	ENERGY STAR

